



Swala WW – IP20 Product number: 11315

SWALA WW FLEXIBLE LED STRIP - SINGLE - RGB - SMD5050 30LED P/M

The Swala WW LED strip from Colorgetix Colorlines series is very user friendly. The Swala WW LED strip emits a warm white light and is perfect for illuminating stores and public spaces. The LED lighting strip consists of 30 type SMD 5050 LEDs per meter. The LED strip has an IP level of IP20 and is therefore not water resistant. When you choose the Swala WW LED strip from the Colorgetix Colorlines series, you are guaranteed to receive a product of high quality.

COLORGETIX COLORLINES SWALA WW LED STRIP ILLUMINATION

The Swala WW LED strip from the Colorgetix Colorlines series, is adjustable to the desired illumination level and has a voltage of 24v DC. Colorgetix has a large range of LED lighting dimming and controlling equipment. With this you can easily adjust the LED lighting to your desired level. The Swala WW LED strip can be dimmed with the Gallo 0-10v LED dimming equipment from the Colorgetix Colorcontroller series. This can be controlled with every 0-10 volts potentiometer. To connect the Swala WW LED strip, a LED lighting driver from the Colordriver series is needed. The right Colorgetix Colordriver for LED lighting depends on the length of the LED strip in meters, and the amount of watts per meter on the LED strip; *The length of the LED strip in meters x The amount of watts per meter = The necessary watts for the driver*. Caution! Always add an extra 10% to the amount of watts needed, there is no maximum amount of watts allowed, but the driver may never have a too low operating capacity.

INSTALLING THE COLORGETIX COLORLINES SWALA WW LED LIGHTING STRIP

To attach the Colorgetix Swala WW LED strip, you only have to remove the 3M layer on the backside of the LED strip. Because of the Swala WW LED strips' flexibility, it also possible to install it in a circular way. Make sure the surface is free of grease and dust, in order to attach the LED strip properly. The Swala WW LED strip is delivered per 5 meters, but can easily be cut to size per 10 cm. If needed, Colorgetix can deliver special LED placement profiles, which gives even more possibilities in attaching LED strips. Colorgetix offers the possibility to solder the LED strip to a preferred size.


WARRANTY

ColorGetix pays the utmost attention to its products, which quality is constantly monitored. Our products have a long life, but how small the chance is, it can always happen that a product fails. For products that do not seem to work, by manufacturing faults or because of us, we will provide a replacement product within the warranty period. If the product stops working due to improper use and we have come to remedy the problems, then we are forced to make charges. ColorGetix not be liable for any consequential damages.

Colorgetix has a wide range of LED lighting and offers a wide range of possibilities for various lighting projects. If you choose Colorgetix, you are assured of reliable and high quality products. Colorgetix can deliver the LED strip in a plug & play manner.

Specifications

Capacity:	7,2 W per meter
Type of LED:	SMD5050
Amount of LED's:	30 per meter
Beam angle:	120 °
Shortest cut distance:	10 cm
IP Norm:	IP 20
Ampère (max):	0.3 Ampère per meter
Voltage:	24V DC
Maximum to connect:	5 Ampère
Length:	Role 5 meter
Width:	10 mm
Height:	2 mm



24 Volt		Cable inner conductor 1.5mm ²					Cable inner conductor 2.5mm ²					Cable inner conductor 4mm ²				
Watt		24	48	72	96	120	144	168	192	216	240	264	288	312	336	360
Cable length (m)	Ampère	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
1																
2																
3																
4																
5																
6																
7																
8																
9																
10																
11																
12																
13																
14																
15																
16																
17																
18																
19																
20																
21																
22																
23																
24																
25																
26																
27																
28																
29																
30																
31																
32																
33																
34																
35																
36																
37																
38																
39																
40																
41																
42																
43																
44																
45																
46																
47																
48																
49																
50																



This table is a recommendation for the cable guide surface (MM²) with cable lengths of 1-50 m. For 24 Volt LED connected in parallel fixtures (voltage controlled). Note that this table is a recommendation, accountability is at all times for the installing person.
If necessary, use the law of Pouillet, ($A \times R = p \times l$) the calculation of electrical conductivity and resistance.

Keep as much as possible the shortest way for 24Volt cables.
Transformer capacity must be 10% higher than the sum of taxes.

When using this table always handle full power (wattage).
So assuming that all the LEDs light up fully to the strips.

$$P = U \times I$$

(Power = voltage (24 volts) times the current)

P (Watts) = U (voltage) times I (ampere)